



## ► Twine tying machines

Cercleurop offers you a range of twine tying machines for quick, safe and reliable tying. There are two lines of machine to choose from: the “closed bottom machine” and the “tunnel”.

### CLOSED BOTTOM MACHINE



- For flat packages.
- Ties with 1, 2 or 3 turns or crossed turns.
- Sturdy, high-performance machines.

Machine type	Size of package to be tied			Feeding
	Length	Height	Depth	
S42E	420	350	275	MONO
S45	450	300	240	TRI
S55	550	550	310	TRI
S65	650	650	320	TRI
S80	800	800	380	TRI
S100	1,000	1,000	340	TRI

### TUNNELS



- Designed for long packages and easily incorporated into an automated production line.
- Once the packages are placed on the conveyor belts, they enter the “tying” tunnel.
- Operator selects either 1 or 2 turns
- Optional multi-turn function.

Machine types	Size of packages to be tied		Machine weight in kg	
	Length	Height	With press	Without press
T30	300	240	210	-
T50	500	500	282	310
T65	650	650	312	350
T90	900	550	360	397
T90F	900	230	310	-
T1200FS	1,200	270	336	-

## ► Twines



PE 1600

Elastomer

For safe and uniform automatic “tying”, it is important to find a good quality, durable twine. We offer products that have undergone rigorous inspection throughout their manufacturing process, to ensure your safety and the safety of your packages.

Make	Kg/reel	Breaking load	Type
PE 1600	2 kg	12 kg	Polyethylene
Elastomer 1700	1,5 kg	20 kg	Polyamide + rubber
Elastomer 1200	1,5 kg	25 kg	Polyamide + rubber